



CLUTCH #/IN	# OF DISCS	FLYWHEEL MOUNTING	SETUP HEIGHT (NEW)*		SETUP HEIGHT (WORN (.87)*)		BOLT GRIP		OVERALL HEIGHT	
			IN	MM	IN	MM	IN	MM	IN	MM
66-513HX	3	POT	1.370	34.80	1.520	38.61	1.346	34.19	1.706	43.33
66-503HX	3	STEP	1.370	34.80	1.520	38.61	1.446	36.73	1.806	45.87
66-514HX	4	POT	1.653	41.99	1.803	45.80	1.629	41.38	1.989	50.52
66-504HX	4	STEP	1.653	41.99	1.803	45.80	1.729	43.92	2.089	53.06

\* SETUP HEIGHT VARIES SLIGHTLY WITH SPRING AND PRESSURE PLATE COMBINATIONS. SEE [www.tiltontracing.com/TECHNICAL](http://www.tiltontracing.com/TECHNICAL) FOR MORE INFORMATION.

- NOTES:**
1. PRIMARY DIMENSIONS ARE INCHES. SECONDARY DIMENSIONS (MM).
  2. MUST BE USED WITH RADIUS FACED RELEASE BEARINGS. CONTACT DIAMETER RANGE FROM .4mm TO .52mm. .4mm CONTACT DIAMETER HIGHLY RECOMMENDED.
  3. ILLUSTRATED WITH DISC PACK P/N 64185-4-VTV-36. DISCS SOLD SEPARATELY.

TILTON ENGINEERING, INC.  
25 EASY STREET P.O. BOX 1797 BUELTON, CALIFORNIA 94027 USA  
(805) 888-2333 FAX (805) 888-2745

TITLE: **INSTALLATION DRAWING**  
CLUTCH, METALLIC, HEAVY DUTY, OT-II 7.25"

DRAWN: LUND CWD: WAHL SCALE: 1:1 REV: **6389**

P/N: 66-5000X DATE: 8/4/2016 SHEET 1 OF 1 DWG: 6389 REV: **NC**

This document contains proprietary information of TILTON ENGINEERING, INC., and its receipt or possession does not convey, through its reproduction, use or sale anything it may describe. Reproduction, disclosure, or use without specific written authorization of TILTON ENGINEERING, INC. is strictly forbidden.

